

ULTIMA™ DTS

The ULTIMA DTS line is the world's highest performing family of Distributed Temperature Sensors, now fanless with enhanced data storage capacity and low power consumption.

The ULTIMA DTS offers the finest temperature resolution and sampling resolutions, from 0.01 °C and 25cm, over a wide operating temperature range. It is a standalone unit with an on-board PC and a user-friendly software interface.

It is available with either 4 or 8 optical channels. The units are optimised for spatial and temperature resolution for the

following ranges: 2/5/10km variable range model M, 10/20/35 km variable range model L. The system can be configured to produce both single-ended and double-ended measurements. Minimum measurement time is 1 second.



Sensing Capabilities

Unit	Range	Channels	Resolution		Measurement Time	Fibre Type	External Reference
			Sampling	Temperature			
ULTIMA M	Up to 10 km	4 or 8	25/50cm	0.01°C	≥1 sec	50/125µm multimode	2 x Pt-100 probes
ULTIMA L	Up to 35 km		1-2 m	0.03°C		9/125µm singlemode	
ULTIMA L-SM	Up to 30 km			0.1°C			

System

Operating system	Windows 10 IoT LTSC		
Network	2 x 1 Gb/s Ethernet		
Storage	Internal SSD [480 GB]		
Control and Data Monitoring	ULTIMA DAQ	Viewer	SDK

Operating Environment

Temperature	-5° to +50°C
Humidity	10-85% Non-condensing

Power Supply Requirements

Nominal voltage range	100 to 240 VAC
Power rating measuring	≤ 60 W
Power rating idle	15 W

Physical Dimensions

Height (feet to lid)	191 mm
Width (brackets closed)	436 mm
Depth	457 mm
Weight	14.1 kg

Compliance

Laser safety	Class 1
Product marking	CE, UKCA and FCC

Silixa Ltd

230, Centennial Park,
Elstree, Hertfordshire

WD6 3SN, UK

t: +44 (0) 20 8327 4210

Silixa LLC

12709 Haynes Road,
Houston

TX 77066, USA

t: +1 713 493 0348

Silixa LLC

3102 W Broadway St,
Suite A, Missoula,

MT 59808, USA

t: +1 406 204 7298

silixa.com

sales@silixa.com

© Silixa Ltd 2025



2021